



ULVAC SMR-100

Material Safety Data Sheet

Revision Date January 2010

For Chemical Emergency Call Chemtrec 800-424-9300

1. Substance/Company Identification	PRODUCT NAME: ULVAC SMR-100 CAS NUMBER: 64742-65-0 DISTRIBUTOR: ULVAC Technologies, Inc. 401 Griffin Brook Drive Methuen, MA 01844 (978) 686-7550
2. Composition/ Ingredients	GENERIC NAME: 100% Solvent refined Neutral paraffinic oil CHEMICAL FORMULA: $(CH_2)_n$ 20 $\leq n \leq$ 40 HAZARDOUS INGREDIENTS: None
3. Hazards Identification	POSSIBLE ENTRY ROUTES: Ingestion, inhalation of oil mists This product is not classified as hazardous. ACUTE EFFECTS: Exposure to oils mists may cause nausea and eye irritation. Detailed studies have not been made, but material is not expected to be dermatitic or a sensitizer. CHRONIC EFFECTS: Unknown.
4. First Aid Measures	SKIN: Wash with soap and water. EYES: Flush with water. Contact a physician! INGESTION: If swallowed, do not induce vomiting. Contact a physician. Small amounts in mouth may be washed out.
5. Fire Fighting Measures	FLASH POINT: 218 C METHOD USED: Cleveland Open Cup EXPLOSIVE LIMITS LOWER: Unknown UPPER: Unknown EXTINGUISHING MEDIA: Water fog, chemical foam or carbon dioxide. NFPA Class III B Material. SPECIAL FIREFIGHTING PROCEDURES: Wear breathing gear when fighting fires in enclosed spaces; incomplete combustion of this material produces carbon monoxide! UNUSUAL FIRE AND/OR EXPLOSION HAZARDS: None
6. Accidental Release Measures	PROCEDURE TO BE FOLLOWED IN EVENT OF RELEASE: Small spills may be wiped up with a rag. Large spills should be picked up immediately with an absorbent.
7. Handling and Storage	HANDLING: None known STORAGE: None known
8. Exposure Controls/Personal Protection	ENGINEERING CONTROL MEASURES: None required RESPIRATORY PROTECTION: See notes on ventilation below. PROTECTIVE GLOVES: Yes - made of oil-impermeable rubber SAFETY GLASSES/GOGGLES: Yes - glasses should have side shields OTHER PROTECTIVE EQUIPMENT: None should be required under normal use.

9. Physical & Chemical Properties

PHYSICAL STATE: Liquid
 VAPOR PRESSURE: $< 1 \times 10^{-4}$ Torr @ 25C
 BOILING POINT: > 200 C
 EVAPORATION RATE (ether = 1): Nil
 VAPOR DENSITY: approximately 14
 WT % VOLATILES: Nil
 SPECIFIC GRAVITY: 0.87
 VISCOSITY: 50 cst @ 40 C
 SOLUBILITY IN WATER: Nil
 APPEARANCE: Pale yellow viscous liquid with a faint petroleum odor.

10. Stability & Reactivity

STABILITY: Material is stable
 CONDITIONS TO AVOID: Continuous exposure to temperatures > 200 C
 INCOMPATIBILITY (MATERIALS TO AVOID): Strong oxidizers
 HAZARDOUS DECOMPOSITION PRODUCTS: Incomplete combustion may produce carbon monoxide.

11. Toxicological Information

ACUTE ORAL LD50(MG/KG): None known
 ACUTE DERMAL LD50: None
 ACUTE INHALATION: US Gov't 8 hr TWA limit for exposure to oil mists is 5 mg per cubic meter

12. Ecological Information

ENVIRONMENTAL: When used and/or disposed of as indicated, no adverse environmental effects are foreseen.
 MOBILITY: Non-volatile and insoluble in water.
 DEGRADABILITY: Slowly biodegradable in aerobic conditions.

13. Disposal Considerations

Product and packaging must be disposed of in accordance with Federal, State and local regulations.

14. Transport Classification

Not classified as hazardous for transport by air, sea or road.

15. Regulatory Information

None

16. Other Information**NFPA RATING**

FLAMMABILITY	1
HEALTH HAZARD	0
REACTIVITY	0
SPECIAL HAZARD	NONE