

Safety Data Sheet

Revision Date May 2025

HCS 2012 (29 CFR 1910.1200)

FOMBLIN® Y LVAC

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

1.1. Identification of the substance or mixture

Product name : FOMBLIN® Y LVAC
Product grade(s) : 06/6; 14/6; 16/6; 25/6; 300

Molecular weight

Range of values : 1,800 - 3,300

1.2. Use of the Substance/Mixture

Recommended use : - Electronic industry

Electrical industry
 Chemical industry
 For industrial use only.

1.3. Company/Undertaking Identification

Address : SOLVAY SPECIALTY POLYMERS USA, LLC

4500 McGINNIS FERRY ROAD ALPHARETTA GA 30005-3914

USA

1.4. Emergency and contact telephone numbers

Emergency telephone : 1 (800) 424-9300 CHEMTREC ® (USA & Canada)

number

Contact telephone number : (856) 853-8119 (Product information)

(product information):

SECTION 2. HAZARDS IDENTIFICATION

Although OSHA has not adopted the environmental portion of the GHS regulations, this document may include information on environmental classification/labeling.

2.1. Classification of the substance or mixture

Not classified according to HCS 2012 (29 CFR 1910.1200).

2.2. Label elements

No labelling

2.3. Other hazards which do not result in classification

None identified

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substances

Chemical nature : Perfluorinated polyethers

Chemical Name	Identification number	Concentration [%]
1-Propene, 1,1,2,3,3,3-hexafluoro-, oxidized, polymd.	CAS-No.: 69991-67-9	> 99.9 %

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

3.2 Mixtures

Not applicable, this product is a substance

SECTION 4. FIRST AID MEASURES

4.1. Inhalation

- Move to fresh air in case of accidental inhalation of fumes from overheating or combustion.
- Oxygen or artificial respiration if needed.

4.2. Eye contact

- Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- If eye irritation persists, consult a specialist.

4.3. Skin contact

- Wash off with soap and water.

4.4. Ingestion

- Drink 1 or 2 glasses of water.
- Do NOT induce vomiting.
- If symptoms persist, call a physician.

SECTION 5. FIREFIGHTING MEASURES

5.1. Suitable extinguishing media

- Water
- powder
- Foam
- Dry chemical

• Carbon dioxide (CO2)

5.2. Extinguishing media which shall not be used for safety reasons

None

5.3. Special exposure hazards in a fire

- The product is not flammable.
- Not explosive
- In case of fire hazardous decomposition products may be produced such as: Gaseous hydrogen fluoride (HF), Fluorophosgene

5.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF).
- Fluorophosgene
- The release of other hazardous decomposition products is possible.

5.5. Special protective equipment for firefighters

- Wear self-contained breathing apparatus and protective suit.
- When intervention in close proximity wear acid resistant over suit.

5.6. Other information

- Evacuate personnel to safe areas.
- Approach from upwind.
- Protect intervention team with a water spray as they approach the fire.
- Keep containers and surroundings cool with water spray.
- Keep product and empty container away from heat and sources of ignition.

SECTION 6. ACCIDENTAL RELEASE MEASURES

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. Advice for non-emergency personnel

Prevent further leakage or spillage if safe to do so.

6.1.2. Advice for emergency responders

- Ensure adequate ventilation.
- Material can create slippery conditions.
- Sweep up to prevent slipping hazard.
- Keep away from open flames, hot surfaces and sources of ignition.

6.2. Environmental precautions

- Should not be released into the environment.
- The product should not be allowed to enter drains, water courses or the soil.
- In case of accidental release or spill, immediately notify the appropriate authorities if required by Federal, State/Provincial and local laws and regulations.

6.3. Methods and materials for containment and cleaning up

- Soak up with inert absorbent material.
- Suitable material for picking up

HCS 2012 (29 CFR 1910.1200)

FOMBLIN® Y LVAC

- Dry sand
- Earth
- Shovel into suitable container for disposal.

6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7. HANDLING AND STORAGE

7.1. Handling

- Ensure adequate ventilation.
- Use personal protective equipment.
- Keep away from heat and sources of ignition.
- To avoid thermal decomposition, do not overheat.
- Take measures to prevent the build up of electrostatic charge.
- Clean and dry piping circuits and equipment before any operations.
- Ensure all equipment is electrically grounded before beginning transfer operations.

7.2. Storage

- Keep away from heat and sources of ignition.
- Keep in properly labelled containers.
- Keep away from combustible material.
- Keep away from incompatible products

7.3. Packaging material

Polyethylene

7.4. Other information

- Provide tight electrical equipment well protected against corrosion.
- Refer to protective measures listed in sections 7 and 8.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Exposure Limit Values

Remarks:

Threshold limit values of by-products from thermal decomposition

Hydrogen fluoride anhydrous

- US. ACGIH Threshold Limit Values 03 2013

time weighted average = 0.5 ppm

Remarks: as F

US. ACGIH Threshold Limit Values 03 2013

Ceiling Limit Value = 2 ppm

Remarks: as F

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

time weighted average = 3 ppm

Remarks: as F

HCS 2012 (29 CFR 1910.1200)

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

Short term exposure limit = 6 ppm

Remarks: as F

US. ACGIH Threshold Limit Values 03 2013

Remarks: as F, Can be absorbed through skin.

US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006

time weighted average = 3 ppm

- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006

Permissible exposure limit = 2.5 mg/m3

Remarks: as F

US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

time weighted average = 3 ppm

Remarks: as F

- <u>US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008</u>

Short term exposure limit = 6 ppm

Remarks: as F

Carbonyl difluoride

US. ACGIH Threshold Limit Values 03 2013

time weighted average = 2 ppm

US. ACGIH Threshold Limit Values 03 2013

Short term exposure limit = 5 ppm

- US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

time weighted average = 2 ppm

time weighted average = 5 mg/m3

US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989

Short term exposure limit = 5 ppm

Short term exposure limit = 15 mg/m3

- US. OSHA Table Z-2 (29 CFR 1910.1000) 02 2006

time weighted average = 2.5 mg/m3

Remarks: Dust

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006

Permissible exposure limit = 2.5 mg/m3

Remarks: as F

US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

time weighted average = 2 ppm

time weighted average = 5 mg/m3

- US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008

Short term exposure limit = 5 ppm

Short term exposure limit = 15 mg/m3

8.2. Engineering controls

- Provide local ventilation appropriate to the product decomposition risk (see section 10).
- Refer to protective measures listed in sections 7 and 8.
- Apply technical measures to comply with the occupational exposure limits.
- For additional information, consult the current edition of The Guide to the Safe Handling of Fluoropolymers published by the Society of Plastics Industry, Inc. (SPI) Fluoropolymer Division.

8.3. Personal protective equipment

8.3.1. Respiratory protection

- No personal respiratory protective equipment normally required.
- Use respirator when performing operations involving potential exposure to vapour of the product.
- Use only respiratory protection that conforms to international/ national standards.
- Use NIOSH approved respiratory protection.
- Comply with OSHA respiratory protection requirements.

8.3.2. Hand protection

- Latex gloves
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

8.3.3. Eye protection

- Safety glasses with side-shields
- If splashes are likely to occur, wear: Tightly fitting safety goggles

8.3.4. Skin and body protection

- Long sleeved clothing
- Safety shoes

8.3.5. Hygiene measures

- Ensure that eyewash stations and safety showers are close to the workstation location.
- When using, do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. General Information

Appearance : liquid
Colour : colourless
Odour : odourless

9.2. Important health safety and environmental information

Boiling point/boiling range : $> 270 \, ^{\circ}\text{C} \, (518 \, ^{\circ}\text{F})$

Flash point : Remarks: The product is not flammable.
Flammability : Remarks: The product is not flammable.

Explosive properties : <u>Explosion danger</u>

Remarks: Not explosive

SAFETY DATA SHEET

HCS 2012 (29 CFR 1910.1200)

FOMBLIN® Y LVAC

Oxidizing properties : Remarks: Non oxidizer

Vapour pressure : 0.0000001 - 0.000013 hPa

Temperature: 20 °C (68 °F)

Relative density / Density : 1.88 - 1.90

1.88 - 1.90 g/cm3

Solubility(ies) Water

> Remarks: insoluble fluorinated solvents Remarks: soluble

Viscosity : ca. 95 - 560 mPa.s

Temperature: 20 °C (68 °F)

9.3. Other data

Melting point/range : Remarks: Not applicable **Decomposition**

temperature

: > 290 °C (554 °F)

SECTION 10. STABILITY AND REACTIVITY

10.1. Stability

Stable under recommended storage conditions.

10.2. Conditions to avoid

- Avoid to use in presence of high voltage electric arc and in absence of oxygen.
- Keep away from flames.
- To avoid thermal decomposition, do not overheat.

10.3. Materials to avoid

- Lewis acids (Friedel-Crafts) above 100°C
- Aluminum and magnesium in powder form above 200°C
- Metals promote and lower decomposition temperature

10.4. Hazardous decomposition products

- Gaseous hydrogen fluoride (HF)., Fluorophosgene
- The release of other hazardous decomposition products is possible.

SECTION 11. TOXICOLOGICAL INFORMATION

11.1. Acute toxicity

Acute oral toxicity

LD50, Rat, > 15,000 mg/kg

Acute inhalation toxicity

No data available

Acute dermal toxicity

LD50, Rat, > 5,000 mg/kg

11.2. Skin corrosion/irritation

- Rabbit, No skin irritation
- Rabbit, No skin irritation, 14 days

11.3. Serious eye damage/eye irritation

- Rabbit, No eye irritation

11.4. Respiratory or skin sensitisation

- Guinea pig, Did not cause sensitisation on laboratory animals., Skin

11.5. Germ cell mutagenicity

- Not mutagenic in Ames Test.
- negative, Chromosome aberration test in vitro

11.6. Carcinogenicity

11.7. Reproductive toxicity

No data available

11.8. Specific target organ toxicity - single exposure

- Remarks: No data available

11.9. Specific target organ toxicity - repeated exposure

- Remarks: No data available

11.10. Aspiration hazard

No data available

11.11. Other information

- Description of possible hazardous to health effects is based on experience and/or toxicological characteristics of several components.
- The thermal decomposition vapours of fluorinated polymers may cause polymer fume fever with flu-like symptoms in humans, especially when smoking contaminated tobacco.
- Thermal decomposition can lead to release of toxic and corrosive gases.
- Exposure to decomposition products
- Causes severe irritation of eyes, skin and mucous membranes.

SECTION 12. ECOLOGICAL INFORMATION

12.1. Ecotoxicity effects

Acute toxicity

 Fishes, Brachydanio rerio, LC50, 96 h, > 360 mg/l Remarks: saturated aqueous solution

- Daphnia magna (Water flea), EC50, 48 h, > 360 mg/l

Remarks: saturated aqueous solution

12.2. Mobility

Remarks: No data available

12.3. Persistence and degradability

Abiotic degradation

- Result: No data available

Biodegradation

- Remarks: non-biodegradable

12.4. Bioaccumulative potential

- Result: No data available

12.5. Other adverse effects

No data available

12.6. Remarks

- Ecological injuries are not known or expected under normal use.

SECTION 13. DISPOSAL CONSIDERATIONS

13.1. Waste from residues / unused products

- Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.
- Waste characterizations and compliance with applicable laws and regulations are the responsibility of the waste generator.
- Can be incinerated, when in compliance with local regulations.
- The incinerator must be equipped with a system for the neutralisation or recovery of HF.

13.2. Packaging treatment

Empty containers can be landfilled, when in accordance with the local regulations.

13.3. RCRA Hazardous Waste

- Listed RCRA Hazardous Waste (40 CFR 302) - No

SECTION 14. TRANSPORT INFORMATION

- Sea (IMO/IMDG)
- not regulated
- Air (ICAO/IATA)
- not regulated
- U.S. Dept of Transportation
- not regulated
- It is recommended that ERG Guide number 111 be used for all non-regulated material.
- Canadian Transportation of Dangerous Goods
- not regulated

SECTION 15. REGULATORY INFORMATION

15.1. Inventory Information

USA. Toxic Substances Control Act (TSCA)	: - Listed on inventory.
Australia. Inventory of Chemical Substances (AICS)	: - Listed on inventory.
Canada. Domestic Substances List (DSL)	: - Listed on inventory.
Korea. Existing Chemicals Inventory (KECI (KR))	: - Listed on inventory.
China. Inventory of Existing Chemical Substances (IECSC)	: - Listed on inventory.
Japan. Industrial Safety & Health Law Inventory (ISHL (JP))	: - Listed on inventory.
Japan. Inventory of Existing & New Chemical Substances (ENCS)	: - Listed on inventory.
Philippine. Inventory of Chemicals and Chemical Substances (PICCS)	: - Listed on inventory.
New Zealand. Inventory of Chemicals (NZIOC)	: - Listed on inventory.
Taiwan. National Existing Chemical Substance Inventory (NECSI)	: - Listed on inventory.
EU. European Registration, Evaluation, Authorisation and Restriction of Chemical (REACH)	: - If product is purchased from Solvay in Europe it is in compliance wit REACH, if not please contact the supplier

15.2. Other regulations

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

- not regulated.

SARA Hazard Designation (SARA 311/312)

- Acute Health Hazard: No.
- Chronic Health Hazard: No.
- Fire Hazard: No.
- Reactivity Hazard: No.
- Sudden Release of Pressure Hazard: No.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

not regulated

US. EPA CERCLA Hazardous Substances (40 CFR 302)

not regulated.

US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5)

not regulated.

US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

not regulated.

US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)

 This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm..

OSHA Hazard communication standard

- This material is non-hazardous as defined by the American OSHA Hazard Communication Standard.

SECTION 16. OTHER INFORMATION

Further information

- New (SDS)
- Distribute new edition to clients
- Date prepared 09/19/2014

Material Safety Data Sheets contain country specific regulatory information; therefore, the MSDS's provided are for use only by customers of the company mentioned in section 1 in North America. If you are located in a country other than Canada, Mexico or the United States, please contact the Solvay Group company in your country for MSDS information applicable to your location.

SAFETY DATA SHEET HCS 2012 (29 CFR 1910.1200)

FOMBLIN® Y LVAC

The previous information is based upon our current knowledge and experience of our product and is not exhaustive. It applies to the product as defined by the specifications. In case of combinations or mixtures, one must confirm that no new hazards are likely to exist. In any case, the user is not exempt from observing all legal, administrative and regulatory procedures relating to the product, personal hygiene, and integrity of the work environment. (Unless noted to the contrary, the technical information applies only to pure product).

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither the company mentioned in section 1 nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. This information gives typical properties only and is not to be used for specification purposes. The company mentioned in section 1 reserves the right to make additions, deletions or modifications to the information at any time without prior notification.

Trademarks and/or other products of the company mentioned in section 1 referenced herein are either trademarks or registered trademarks of the company mentioned in section 1 or its affiliates, unless otherwise indicated.

Copyright 2014, Company mentioned in Section 1. All Rights Reserved.

